

## Treston trusts Tango



We manufacture high-quality industrial furniture and workstations in Finland, and we demand the same level of excellence from all our components, including castors. We supply furniture all over the world, which means that our products need to meet the global quality requirements in different operating environments, such as the EPA. The wide range of castors, continuous product development and effortless cooperation have been the cornerstones of our decades-long cooperation with Manner. Several of our trolley models are equipped with Tango castors, as they not only fit the visual appearance but also offer top quality performance. Tango meets all our most important criteria, such as safety, cleanability and portability (trolley maximum load 300 kg) with ease.



JONNA PATAMA | PRODUCT GROUP MANAGER | TRESTON OY



**The wide range of castors, continuous product development and effortless cooperation have been the cornerstones of our decades-long cooperation with Manner.**



## Superior Tango castor

- ✓ Multiple fitting options
- ✓ Secure, protective brake pedal
- ✓ World-renowned design – good-looking and easy to clean
- ✓ Sealed, protected ball bearings – stable and smooth rolling
- ✓ Easy to fit with standard tools
- ✓ Suitable for multiple applications and circumstances
- ✓ Multiple tread material options



## COLSON Castors & Wheels for every application

Since the beginning of 2023, OY Mannerin Konepaja Ab in Finland has been part of the Colson Group, the world's largest manufacturer of castors and wheels. The internationally active group of companies includes more than 20 companies in the castor industry, so that a particularly wide range of products can be offered.

The product range contains for example furniture castors, apparatus castors, medical-technical castors, transport castors, stainless steel castors or heavy-duty castors with a wide variety of housings, fittings and wheels for every application.

Find out more about our extensive product range on our website [www.colson-rollen.com](http://www.colson-rollen.com) or get in touch with us by phone.



Colson Rollen GmbH, Industriestraße 8, D-42499 Hückeswagen, [info@colson-rollen.com](mailto:info@colson-rollen.com)  
Tel.: +49 2192 9368-0, Fax: +49 2192 9368-477, [www.colson-rollen.com](http://www.colson-rollen.com)

TANGO SERIES  
MEDICAL

Ø 75-125 MM  
CATERING

70-100 KG  
INSTITUTIONAL

# Tango

Adaptable equipment castor



# Tango – for use in different environments

Special — often demanding — applications set specific requirements even for equipment castors. The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic.

The smoothly rolling and maintenance-free Tango is manufactured of glass fibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



Stainless

Conductive

Non-magnetic



## Looks matter

The standard colour of the Tango castor is grey (RAL 7042) with red brake pedal. The smaller of the two pedal options is the standard model and the larger one is the special model. The larger pedal, customer-specific special colours and company logo on the brake pedal are available for orders of larger quantities. Contact us for more information.



## Multiple alternatives

Tango equipment castors are available in three sizes: 75 mm, 100 mm and 125 mm. Tread material and hardness can be selected from a number of options. The standard fitting solutions are a threaded stem, a rectangular top plate and an expander. Stem fittings are available as a special product. The structure of the fork enables easy fitting with standard tools.



### FEATURES:

- Wheel diameters: 75, 100 and 125 mm
- Range of castors: swivel castor, swivel castor with total-stop brake, directional lock or fixed castor (100 and 125 mm)
- Options: stainless, conductive, non-magnetic
- Heights: 110–168 mm
- Load capacity: 70–100 kg
- Tread material options for different applications and surfaces
- Wheel bearing: ball bearing
- Additional appliances and special solutions: ask for additional information



75 mm

100 mm

125 mm