

# Medical products Europe

Catalogue



**manner**  
SMART MOVES ON MANNER CASTORS

**MedCaster**  
Product Line

## PRODUCT OVERVIEW



### Tango series

- Plastic single wheel castor
- Housing in glass-fibre reinforced polyamide
- Precision ball bearing both in swivel head and wheel centre
- **Diameters:** 75, 100, 125 mm
- **Load capacity:** 70–100 kg
- **Standard:** EN 12530
- **Applications:** Medical carts, shower chairs, standing/seating systems, walking aids recliners, hoists, mobile working stations



### Twist series

- Plastic twin wheel castor
- Housing in glass-fibre reinforced polyamide
- Precision ball bearing both in swivel head and wheel centre
- **Diameters:** 75, 100, 125 mm
- **Load capacity:** 80–125 kg
- **Standard:** EN 12530
- **Applications:** Medical carts, hoists, patient transfer products mobile work stations, shower chairs, operating room equipment seating/standing systems, incubators, medical chairs, ultra low beds
- **NEW – Twist CL series**  
Now also available with central locking.



### Genesis (PGE) series

- Plastic single wheel castor
- Housing in polyamide
- Ball bearing in wheel
- **Diameter:** 75, 100 mm
- **Load capacity:** up to 100 kg
- **Standard:** EN 12530
- Available also with different fittings: bolt hole, plate, threaded stem and grip ring stem
- Available also in colour grey and black
- **Applications:** medical equipment



### Series 367

- Sheet steel housing
- Housing with bolt hole, plate and stem fastening
- Wheel with ball bearing
- **Diameter:** 80–200 mm
- **Load capacity:** up to 120 kg
- **Standard:** EN 12530
- **Applications:** Medical trolleys and chairs, patient transport equipment, nursing beds

## CENTRAL LOCKING CASTORS



### e-SMART series

- Plastic single wheel with electrical central lock
- Housing in glass-fibre reinforced polyamide
- Precision ball bearing both in swivel head and wheel centre
- **Diameter:** 125 mm
- **Load capacity:** 150 kg
- **Standard:** EN 12531
- **Applications:** Mobile operating tables, surgical tables, hospital beds, other medical equipment



### Vivax HBC series

- Plastic single wheel castor with central lock
- Housing in glass-fibre reinforced polyamide
- Precision ball bearing both in swivel head and wheel centre
- With total lock or total lock and directional lock
- **Diameters:** 125, 150 mm
- **Load capacity:** 130 kg
- **Standard:** EN 12531
- **Applications:** Homecare beds, medical chairs, other medical equipment



### Twintech series

- Die-cast aluminium housing
- Precision ball bearing both in swivel head and wheel centre
- With total lock or total lock and directional lock
- **Diameter:** 125, 150 mm
- **Load capacity:** 135–150 kg
- **Standard:** EN 12531
- **Applications:** Hospital beds, homecare beds, operating tables, other medical equipment



### Primacy series

- Single wheel castor with central locking
- Die-cast aluminium load-bearing housing with plastic cover
- Precision ball bearing both in swivel head and wheel centre
- With total lock or total lock and directional lock
- **Diameters:** 125, 150, 200 mm
- **Load capacity:** 150 kg
- **Standard:** EN 12531
- **Applications:** Hospital beds, homecare beds, operating tables, other medical equipment



### TT and CT series

- Twin wheel castor with central lock
- Precision ball bearing both in swivel head and wheel centre
- With total lock or total lock and directional lock
- **Diameters:** 75, 100, 125, 150 mm
- **Load capacity:** 90–200 kg
- **Standard:** EN 12531
- **Applications:** Hospital beds, homecare beds, operating tables, other medical equipment



### Nimbus series

- Single wheel castor with central locking
- Die-cast aluminium load-bearing housing with plastic cover
- Precision ball bearing both in swivel head and wheel centre
- With total lock or total lock and directional lock
- **Diameter:** 150 mm
- **Load capacity:** 120 kg
- **Standard:** EN 12531
- **Applications:** Hospital beds, homecare beds, operating tables, other medical equipment

## PLUNGER LOCK CASTOR



### Series 403

- Plastic twin wheel castor especially suitable for operating tables
- Housing in glass-fibre reinforced polyamide
- Precision ball bearings in swivel head and wheel centre ensure easy manoeuvrability and smooth positioning
- The assembly is based on a hydraulic system (can be ordered separately).
- **Diameter:** 100 mm
- **Load capacity:** 250 kg
- **Standard:** EN 12531
- **Application:** Operating tables
- **NEW – Series 403b**  
Now also available with single brake.

Please see page 20 for more information

## WHEELCHAIR PRODUCTS



### Wheelchair products

- Plastic wheels and castors with puncture proof tyre
- **Load capacity** 40–60 kg
- **Applications:** Wheelchairs, patient transfer chairs, other medical equipment

Please see pages 21 for more detailed information

## YOUR FIRST CHOICE

## Tango

The Tango is a versatile and adaptable equipment castor that is suitable even for challenging applications. The easy to manoeuvre, maintenance-free Tango is made of glass fibre reinforced polyamide. Thanks to its materials and design, the Tango is corrosion-resistant and easy to clean. Glass-fibre reinforced housing Precision ball bearings in both swivel head and wheel centre ensures easy rolling and turning.



## Twist

TWIST – is an easy to manoeuvre, sturdy and high-quality twin wheel castor. Its special feature is its intuitive brake pedal, which clearly shows the status of the locking system. Thanks to its materials and design, the Twist is corrosion-resistant and easy to clean.

**NEW** – Twist CL series – Now also available with central locking.

## e-SMART Serie

Medical castor with electric central locking. The superior ergonomics and safety of the patented castor locking system improve and facilitate work. The locking/unlocking actuator is embedded in the wheel and connected to the control system. The wheel can be locked and released easily and ergonomically at the push of a button, and the motion sensor allows automatic locking.



reddot design award  
best of the best 2010



The **Tango** is a versatile and adaptable equipment castor that is suitable even for challenging applications. The easy to manoeuvre, maintenance-free Tango is made of glass fibre-reinforced polyamide. Thanks to its materials and design, the Tango is corrosion-resistant and easy to clean. Precision ball bearings in both swivel head and wheel centre ensure easy rolling and turning. Codes ending with PTE/K 80 – polypropylene centre and thermoplastic rubber tread, 80 Sh A. Codes ending with NP/K – polyamide centre and polyurethane tread, 80 Sh A.

SWIVEL - BOLT FIXATION



| Art.nr | Code               |     |    |     |     |       |   |     |
|--------|--------------------|-----|----|-----|-----|-------|---|-----|
| 301743 | GKR-S-75 PTE/K 80  | 75  | 32 | 110 | 73  | 10X16 | • | 70  |
| 304399 | GKR-S-75 NP/K      | 75  | 32 | 110 | 73  | 10X16 | • | 90  |
| 301751 | GKR-S-100 PTE/K 80 | 100 | 32 | 141 | 95  | 10X16 | • | 100 |
| 304000 | GKR-S-100 NP/K     | 100 | 32 | 141 | 95  | 10X16 | • | 100 |
| 301649 | GKR-S-125 PTE/K 80 | 125 | 32 | 161 | 110 | 10X16 | • | 100 |
| 304004 | GKR-S-125 NP/K     | 125 | 32 | 161 | 110 | 10X16 | • | 100 |

TOTAL LOCK - BOLT FIXATION



| Art.nr | Code                 |     |    |     |     |       |   |     |
|--------|----------------------|-----|----|-----|-----|-------|---|-----|
| 301755 | GKR-J-S-75 PTE/K 80  | 75  | 32 | 110 | 94  | 10X16 | • | 70  |
| 304403 | GKR-J-S-75 NP/K      | 75  | 32 | 110 | 94  | 10X16 | • | 90  |
| 301763 | GKR-J-S-100 PTE/K 80 | 100 | 32 | 141 | 95  | 10X16 | • | 100 |
| 304012 | GKR-J-S-100 NP/K     | 100 | 32 | 141 | 95  | 10X16 | • | 100 |
| 301651 | GKR-J-S-125 PTE/K 80 | 125 | 32 | 161 | 110 | 10X16 | • | 100 |
| 304016 | GKR-J-S-125 NP/K     | 125 | 32 | 161 | 110 | 10X16 | • | 100 |

DIRECTIONAL LOCK - BOLT FIXATION



| Art.nr | Code                 |     |    |     |     |       |   |     |
|--------|----------------------|-----|----|-----|-----|-------|---|-----|
| 301767 | GKR-R-S-75 PTE/K 80  | 75  | 32 | 110 | 94  | 10X16 | • | 70  |
| 304407 | GKR-R-S-75 NP/K      | 75  | 32 | 110 | 94  | 10X16 | • | 90  |
| 301775 | GKR-R-S-100 PTE/K 80 | 100 | 32 | 141 | 95  | 10X16 | • | 100 |
| 304024 | GKR-R-S-100 NP/K     | 100 | 32 | 141 | 95  | 10X16 | • | 100 |
| 301707 | GKR-R-S-125 PTE/K 80 | 125 | 32 | 161 | 110 | 10X16 | • | 100 |
| 304028 | GKR-R-S-125 NP/K     | 125 | 32 | 161 | 110 | 10X16 | • | 100 |

The following is applicable to all three castor sizes:

- \* Available also with M12x16 mm threaded stem
- \* Available also with 10 and 12.8 mm bolt hole
- \* For 12.8 mm bolt hole version, please contact us for more details
- \* Available also in conductive version
- \* 100 and 125 mm available also in stainless steel version

SWIVEL - TOP PLATE



| Art.nr | Code               |  |  |  |  |  |  |  |  |     |
|--------|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----|
| 301779 | GKL-S-75 PTE/K 80  | 75                                                                                  | 32                                                                                  | 117                                                                                 | 73                                                                                  | 77X67                                                                               | 61/51X50/42                                                                         | 8                                                                                   | •                                                                                   | 70  |
| 304410 | GKL-S-75 NP/K      | 75                                                                                  | 32                                                                                  | 117                                                                                 | 73                                                                                  | 77X67                                                                               | 61/51X50/42                                                                         | 8                                                                                   | •                                                                                   | 90  |
| 301787 | GKL-S-100 PTE/K 80 | 100                                                                                 | 32                                                                                  | 148                                                                                 | 95                                                                                  | 77X67                                                                               | 61/51X50/42                                                                         | 8                                                                                   | •                                                                                   | 100 |
| 304033 | GKL-S-100 NP/K     | 100                                                                                 | 32                                                                                  | 148                                                                                 | 95                                                                                  | 77X67                                                                               | 61/51X50/42                                                                         | 8                                                                                   | •                                                                                   | 100 |
| 301688 | GKL-S-125 PTE/K 80 | 125                                                                                 | 32                                                                                  | 168                                                                                 | 110                                                                                 | 77X67                                                                               | 61/51X50/42                                                                         | 8                                                                                   | •                                                                                   | 100 |
| 304035 | GKL-S-125 NP/K     | 125                                                                                 | 32                                                                                  | 168                                                                                 | 110                                                                                 | 77X67                                                                               | 61/51X50/42                                                                         | 8                                                                                   | •                                                                                   | 100 |

TOTAL LOCK - TOP PLATE



| Art.nr | Code                 |  |  |  |  |  |  |  |  |  |
|--------|----------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 301791 | GKL-J-S-75 PTE/K 80  | 75                                                                                    | 32                                                                                    | 117                                                                                   | 94                                                                                    | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 70                                                                                    |
| 304412 | GKL-J-S-75 NP/K      | 75                                                                                    | 32                                                                                    | 117                                                                                   | 94                                                                                    | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 90                                                                                    |
| 301799 | GKL-J-S-100 PTE/K 80 | 100                                                                                   | 32                                                                                    | 148                                                                                   | 95                                                                                    | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 100                                                                                   |
| 304039 | GKL-J-S-100 NP/K     | 100                                                                                   | 32                                                                                    | 148                                                                                   | 95                                                                                    | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 100                                                                                   |
| 301697 | GKL-J-S-125 PTE/K 80 | 125                                                                                   | 32                                                                                    | 168                                                                                   | 110                                                                                   | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 100                                                                                   |
| 304041 | GKL-J-S-125 NP/K     | 125                                                                                   | 32                                                                                    | 168                                                                                   | 110                                                                                   | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 100                                                                                   |

DIRECTIONAL LOCK - TOP PLATE



| Art.nr | Code                 |  |  |  |  |  |  |  |  |     |
|--------|----------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|-----|
| 301803 | GKL-R-S-75 PTE/K 80  | 75                                                                                    | 32                                                                                    | 117                                                                                   | 73                                                                                    | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 80  |
| 304414 | GKL-R-S-75 NP/K      | 75                                                                                    | 32                                                                                    | 117                                                                                   | 94                                                                                    | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 90  |
| 301811 | GKL-R-S-100 PTE/K 80 | 100                                                                                   | 32                                                                                    | 148                                                                                   | 95                                                                                    | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 100 |
| 304045 | GKL-R-S-100 NP/K     | 100                                                                                   | 32                                                                                    | 148                                                                                   | 95                                                                                    | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 100 |
| 301715 | GKL-R-S-125 PTE/K 80 | 125                                                                                   | 32                                                                                    | 168                                                                                   | 110                                                                                   | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 100 |
| 304047 | GKL-R-S-125 NP/K     | 125                                                                                   | 32                                                                                    | 168                                                                                   | 110                                                                                   | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 100 |

All top plate versions available in conductive version




FIXED - BOLT FIXATION

| Art.nr | Code               |     |    |     |       |   |     |
|--------|--------------------|-----|----|-----|-------|---|-----|
| 301033 | GPR-S-100 PTE/K 80 | 100 | 32 | 141 | 10x16 | • | 100 |
| 304049 | GPR-S-100 NP/K     | 100 | 32 | 141 | 10x16 | • | 100 |
| 301037 | GPR-S-125 PTE/K 80 | 125 | 32 | 161 | 10x16 | • | 100 |
| 304051 | GPR-S-125 NP/K     | 125 | 32 | 161 | 10x16 | • | 100 |



FIXED - TOP PLATE

| Art.nr | Code               |     |    |     |       |             |   |   |     |
|--------|--------------------|-----|----|-----|-------|-------------|---|---|-----|
| 301041 | GPL-S-100 PTE/K 80 | 100 | 32 | 141 | 77X67 | 61/51X50/42 | 8 | • | 100 |
| 304053 | GPL-S-100 NP/K     | 100 | 32 | 141 | 77X67 | 61/51X50/42 | 8 | • | 100 |
| 301045 | GPL-S-125 PTE/K 80 | 125 | 32 | 161 | 77X67 | 61/51X50/42 | 8 | • | 100 |
| 304055 | GPL-S-125 NP/K     | 125 | 32 | 161 | 77X67 | 61/51X50/42 | 8 | • | 100 |



BUMPER WHEEL

| Art.nr | Code           |    |    |
|--------|----------------|----|----|
| 303956 | TSGK-90 PTE    | 90 | 10 |
| 303957 | TSGK-90 PTE-12 | 90 | 12 |

Polypropylene centre + thermoplastic tread, 70 Sh A  
Please note that the bumper wheel elevates the overall height by 5 mm

Genesis (PGE) – is a high-strength medical castor with a precision ball bearing for swiveling. Made from polyamide, it ensures durability and corrosion resistance against all known detergents and chemicals. Soft (Shore A 65) non-marking Monotech wheels reject debris and provide excellent navigation on both carpet and hard floors.



SWIVEL – TOP PLATE

| Code                 |     |    |     |    |       |          |   |   |     |
|----------------------|-----|----|-----|----|-------|----------|---|---|-----|
| PGE40120WH-MNT63(GG) | 100 | 30 | 143 | 95 | 95X67 | 76/70x45 | 8 | • | 100 |

\*Available also in other colours (grey & black)  
\*Also available in diameter 75 mm  
\*Different fittings available: plate (diameter 100 mm), threaded stem & grip ring stem (diameter 75, 100 mm)



WHEEL BRAKE – TOP PLATE

| Code                  |     |    |     |     |       |          |   |   |     |
|-----------------------|-----|----|-----|-----|-------|----------|---|---|-----|
| PGE40120WH-MNT63(GG)B | 100 | 30 | 143 | 105 | 95X67 | 76/70x45 | 8 | • | 100 |

\*Available also in other colours (grey & black)  
\*Also available in diameter 75 mm  
\*Different fittings available: plate (diameter 100 mm), threaded stem & grip ring stem (diameter 75, 100 mm)



Available also in other colours and with different fittings  
(plate, threaded stem, grip ring stem).

The **Series 367** is a robust and individually applicable equipment castor that is suitable even for challenging application areas. The easy to manoeuvre, maintenance-free sheet steel castor is zinc passivated and has a swivel bearing with double-row ball race in the fork head. Possible fastenings are: plate, back hole, stem and expansion sleeve fastenings. The TPE wheels (Shore A 80) with plastic wheel body and plastic thread guard as well as precision ball bearings are suitable for a wide range of applications. For special applications, other wheel variants and conductive TPU tyres are available.

SWIVEL CASTOR WITH PLATE



| Code              |     |    |       |       |             |   |   |     |
|-------------------|-----|----|-------|-------|-------------|---|---|-----|
| 367a 29K080r ZP95 | 80  | 30 | 117   | 95x70 | 75x45/72x52 | 9 | • | 100 |
| 367a 29K100r ZP95 | 100 | 30 | 138   | 95x70 | 75x45/72x52 | 9 | • | 100 |
| 367a 29K125r ZP95 | 125 | 32 | 162,5 | 95x70 | 75x45/72x52 | 9 | • | 100 |
| 367a 29K150r ZP95 | 150 | 32 | 189   | 95x70 | 75x45/72x52 | 9 | • | 120 |
| 367a 29K200r ZP95 | 200 | 32 | 241   | 95x70 | 75x45/72x52 | 9 | • | 120 |

SWIVEL CASTOR WITH TOTAL LOCK AND PLATE



| Code              |     |    |       |       |             |   |   |     |
|-------------------|-----|----|-------|-------|-------------|---|---|-----|
| 367h 29K080r ZP95 | 80  | 30 | 117   | 95x70 | 75x45/72x52 | 9 | • | 100 |
| 367h 29K100r ZP95 | 100 | 30 | 138   | 95x70 | 75x45/72x52 | 9 | • | 100 |
| 367h 29K125r ZP95 | 125 | 32 | 162,5 | 95x70 | 75x45/72x52 | 9 | • | 100 |
| 367h 29K150r ZP95 | 150 | 32 | 189   | 95x70 | 75x45/72x52 | 9 | • | 120 |
| 367h 29K200r ZP95 | 200 | 32 | 241   | 95x70 | 75x45/72x52 | 9 | • | 120 |

FIXED CASTOR



| Code              |     |    |       |       |             |   |   |     |
|-------------------|-----|----|-------|-------|-------------|---|---|-----|
| 367r 29K080r ZP95 | 80  | 30 | 117   | 95x70 | 75x45/72x52 | 9 | • | 100 |
| 367r 29K100r ZP95 | 100 | 30 | 138   | 95x70 | 75x45/72x52 | 9 | • | 100 |
| 367r 29K125r ZP95 | 125 | 32 | 162,5 | 95x70 | 75x45/72x52 | 9 | • | 100 |
| 367r 29K150r ZP95 | 150 | 32 | 189   | 95x70 | 75x45/72x52 | 9 | • | 120 |
| 367r 29K200r ZP95 | 200 | 32 | 241   | 95x70 | 75x45/72x52 | 9 | • | 120 |

Also available with expansion sleeve fastening.

All castors on this page are also available in conductive versions.

SWIVEL CASTOR WITH BOLT HOLE



| Code              |     |    |       |      |   |     |
|-------------------|-----|----|-------|------|---|-----|
| 367a 29K080r ZL12 | 80  | 30 | 110   | 12,2 | • | 100 |
| 367a 29K100r ZL12 | 100 | 30 | 131   | 12,2 | • | 100 |
| 367a 29K125r ZL12 | 125 | 32 | 155,5 | 12,2 | • | 100 |
| 367a 29K150r ZL12 | 150 | 32 | 182   | 12,2 | • | 120 |
| 367a 29K200r ZL12 | 200 | 32 | 234   | 12,2 | • | 120 |

SWIVEL CASTOR WITH TOTAL LOCK AND BOLT HOLE



| Code              |     |    |       |      |   |     |
|-------------------|-----|----|-------|------|---|-----|
| 367h 29K080r ZL12 | 80  | 30 | 110   | 12,2 | • | 100 |
| 367h 29K100r ZL12 | 100 | 30 | 131   | 12,2 | • | 100 |
| 367h 29K125r ZL12 | 125 | 32 | 155,5 | 12,2 | • | 100 |
| 367h 29K150r ZL12 | 150 | 32 | 182   | 12,2 | • | 120 |
| 367h 29K200r ZL12 | 200 | 32 | 234   | 12,2 | • | 120 |

SWIVEL CASTOR WITH STEM



| Code                 |     |    |       |             |   |     |
|----------------------|-----|----|-------|-------------|---|-----|
| 367a 29K080r ZZ24x45 | 80  | 30 | 112   | 24x45 M8/19 | • | 100 |
| 367a 29K100r ZZ24x45 | 100 | 30 | 133   | 24x45 M8/19 | • | 100 |
| 367a 29K125r ZZ24x45 | 125 | 32 | 157,5 | 24x45 M8/19 | • | 100 |
| 367a 29K150r ZZ24x45 | 150 | 32 | 184   | 24x45 M8/19 | • | 120 |
| 367a 29K200r ZZ24x45 | 200 | 32 | 236   | 24x45 M8/19 | • | 120 |

SWIVEL CASTOR WITH TOTAL LOCK AND STEM



| Code                 |     |    |       |             |   |     |
|----------------------|-----|----|-------|-------------|---|-----|
| 367h 29K080r ZZ24x45 | 80  | 30 | 112   | 24x45 M8/19 | • | 100 |
| 367h 29K100r ZZ24x45 | 100 | 30 | 133   | 24x45 M8/19 | • | 100 |
| 367h 29K125r ZZ24x45 | 125 | 32 | 157,5 | 24x45 M8/19 | • | 100 |
| 367h 29K150r ZZ24x45 | 150 | 32 | 184   | 24x45 M8/19 | • | 120 |
| 367h 29K200r ZZ24x45 | 200 | 32 | 236   | 24x45 M8/19 | • | 120 |

**Twist** – is an easy-to-maneuver, sturdy, and high-quality twin-wheel castor. Its standout feature is the intuitive brake pedal, clearly indicating the status of the locking system for added convenience. Crafted from corrosion-resistant materials and designed for easy cleaning, the Twist is as durable as it is practical. With a glass fibre-reinforced polyamide centre and a polyurethane tyre equipped with ball bearings, the Twist delivers smooth operation and reliable performance in any setting. Precision ball bearings in both swivel head and wheel centre. Glass fibre-reinforced polyamide centre + polyurethane tread, 95 Sh A.



SWIVEL - BOLT HOLE

| Art.nr | Code                    |     |      |    |     |     |      |   |     |
|--------|-------------------------|-----|------|----|-----|-----|------|---|-----|
| 305294 | TW-S-75 GP/K H          | 75  | 2X15 | 60 | 80  | 61  | 10,2 | • | 95  |
| 305132 | TW-S-100 GP/K LOW H (*) | 100 | 2X20 | 81 | 106 | 89  | 10,2 | • | 125 |
| 305130 | TW-S-100 GP/K H (*)     | 100 | 2X20 | 81 | 118 | 89  | 10,2 | • | 125 |
| 305014 | TW-S-125 GP/K LOW H (*) | 125 | 2X20 | 81 | 130 | 102 | 10,2 | • | 125 |
| 305010 | TW-S-125 GP/K H (*)     | 125 | 2X20 | 81 | 143 | 102 | 10,2 | • | 125 |

Available also in stainless steel and conductive version  
\*) Available also with 12.8 mm bolt hole



TOTAL LOCK - BOLT HOLE

| Art.nr | Code                      |     |      |    |     |     |      |   |     |
|--------|---------------------------|-----|------|----|-----|-----|------|---|-----|
| 305295 | TW-J-S-75 GP/K H (**)     | 75  | 2X15 | 60 | 80  | 85  | 10,2 | • | 95  |
| 305133 | TW-J-S-100 GP/K LOW H (*) | 100 | 2X20 | 81 | 106 | 113 | 10,2 | • | 125 |
| 305131 | TW-J-S-100 GP/K H (*)     | 100 | 2X20 | 81 | 118 | 113 | 10,2 | • | 125 |
| 305015 | TW-J-S-125 GP/K LOW H (*) | 125 | 2X20 | 81 | 130 | 133 | 10,2 | • | 125 |
| 305011 | TW-J-S-125 GP/K H (*)     | 125 | 2X20 | 81 | 143 | 133 | 10,2 | • | 125 |

Available also in stainless steel and conductive version  
\*) Available also with 12.8 mm bolt hole  
\*\*) 75 mm with wheel brake



DIRECTIONAL LOCK - BOLT HOLE

| Art.nr | Code              |     |      |    |     |     |      |   |     |
|--------|-------------------|-----|------|----|-----|-----|------|---|-----|
| 305378 | TW-R-S-125 GP/K H | 125 | 2X20 | 81 | 130 | 133 | 10,2 | • | 125 |

Available also with 12.8 mm bolt hole  
Available also in stainless steel and conductive version



SWIVEL - TOP PLATE

| Art.nr | Code             |  |  |  |  |  |  |  |  |  |  |
|--------|------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 305301 | TWL-S-75 GP/K H  | 75                                                                                  | 2X15                                                                                | 60                                                                                  | 89                                                                                  | 61                                                                                  | 77X67                                                                               | 61/51X50/42                                                                         | 8                                                                                   | •                                                                                   | 80                                                                                  |
| 305271 | TWL-S-100 GP/K H | 100                                                                                 | 2X20                                                                                | 81                                                                                  | 127                                                                                 | 89                                                                                  | 77X67                                                                               | 61/51X50/42                                                                         | 8                                                                                   | •                                                                                   | 100                                                                                 |
| 305281 | TWL-S-125 GP/K H | 125                                                                                 | 2X20                                                                                | 81                                                                                  | 152                                                                                 | 102                                                                                 | 77X67                                                                               | 61/51X50/42                                                                         | 8                                                                                   | •                                                                                   | 100                                                                                 |

Available also in conductive version



TOTAL LOCK - TOP PLATE

| Art.nr | Code                  |  |  |  |  |  |  |  |  |  |  |
|--------|-----------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 305302 | TWL-J-S-75 GP/K H (*) | 75                                                                                    | 2X15                                                                                  | 60                                                                                    | 89                                                                                    | 85                                                                                    | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 80                                                                                    |
| 305272 | TWL-J-S-100 GP/K H    | 100                                                                                   | 2X20                                                                                  | 81                                                                                    | 127                                                                                   | 113                                                                                   | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 100                                                                                   |
| 305282 | TWL-J-S-125 GP/K H    | 125                                                                                   | 2X20                                                                                  | 81                                                                                    | 152                                                                                   | 133                                                                                   | 77X67                                                                                 | 61/51X50/42                                                                           | 8                                                                                     | •                                                                                     | 100                                                                                   |

Available also in conductive version  
\*) 75 mm with wheel brake



BUMPER WHEEL

| Art.nr | Code             |    |    |
|--------|------------------|----|----|
| 304313 | TSGK-90 PTE H    | 90 | 10 |
| 304314 | TSGK-90 PTE-12 H | 90 | 12 |

\* Polypropylene centre + thermoplastic tread, 70 Sh A  
\* Suitable for 100 and 125 mm castors in high version  
\* Please note that the bumper wheel elevates the overall height by 5 mm



# Twist CL – Central locking



SWIVEL CASTOR WITH CENTRAL TOTAL LOCK

| Art.nr | Code                |     |           |     |    |       |   |     |
|--------|---------------------|-----|-----------|-----|----|-------|---|-----|
| 305875 | TWC-Q-S-100 GP/Z985 | 100 | 2x20 (85) | 104 | 91 | 32x50 | • | 135 |



SWIVEL CASTOR WITH CENTRAL TOTAL LOCK AND DIRECTIONAL LOCK

| Art.nr | Code                |     |           |     |    |       |   |     |
|--------|---------------------|-----|-----------|-----|----|-------|---|-----|
| 305876 | TWC-R-S-100 GP/Z985 | 100 | 2x20 (85) | 104 | 91 | 32x50 | • | 135 |

NEW!



The **e-SMART** – is an equipment castor featuring electric central locking for enhanced convenience and safety in various applications. Its superior ergonomics and safety features are designed to improve and facilitate work processes. With a glass fibre-reinforced polyamide centre and a soft polyurethane tyre (80 Sh A) equipped with ball bearings, the e-SMART ensures durability, smooth operation, and reliable performance.



reddot design award  
best of the best 2010

Castors must be connected to a control system which controls their functions.  
Contact us for more detailed information.



**SWIVEL CASTOR WITH ELECTRIC CENTRAL LOCKING**  
**ELECTRIC CENTRAL LOCKING LOCKS WHEEL AND SWIVEL**

Mounting into a rectangular mounting tube with external dimensions of 50x50 mm

| Art.nr | Code                   |     |    |     |     |       |   |     |
|--------|------------------------|-----|----|-----|-----|-------|---|-----|
| 302962 | FK50X50-EJ-S-125 GPF/K | 125 | 32 | 172 | 105 | 46X46 | • | 150 |

\* Available also in conductive version upon MOQ



**SWIVEL CASTOR WITH ELECTRIC DIRECTIONAL LOCKING**  
**ELECTRIC DIRECTIONAL LOCK LOCKS THE CASTOR IN THE DIRECTION OF TRAVEL**

Mounting into a rectangular mounting tube with external dimensions of 50x50 mm

| Art.nr | Code                     |     |    |     |     |       |   |     |
|--------|--------------------------|-----|----|-----|-----|-------|---|-----|
| 302974 | FK50X50-ER-S-125 GPF/K   | 125 | 32 | 172 | 105 | 46X46 | • | 150 |
| 302977 | FK50X50-ER90-S-125 GPF/K | 125 | 32 | 172 | 105 | 46X46 | • | 150 |

\* Two models, depending on how the mounting tube is in relation to the direction of travel.

\* Available also in conductive version upon MOQ



**SWIVEL CASTOR WITH ELECTRIC CENTRAL LOCKING**  
**ELECTRIC CENTRAL LOCKING LOCKS WHEEL AND SWIVEL**

Mounting into a round mounting tube with external diameter of 60 mm

| Art.nr | Code                |     |    |     |     |      |   |     |
|--------|---------------------|-----|----|-----|-----|------|---|-----|
| 302975 | FK60-EJ-S-125 GPF/K | 125 | 32 | 167 | 105 | 54,5 | • | 150 |

\* Available also in conductive version upon MOQ




**SWIVEL CASTOR WITH ELECTRIC DIRECTIONAL LOCKING**  
**ELECTRIC DIRECTIONAL LOCK LOCKS THE CASTOR IN THE DIRECTION OF TRAVEL**

Mounting into a round mounting tube with external diameter of 60 mm

| Art.nr | Code                  |     |    |     |     |      |   |     |
|--------|-----------------------|-----|----|-----|-----|------|---|-----|
| 302976 | FK60-ER-S-125 GPF/K   | 125 | 32 | 167 | 105 | 54,5 | • | 150 |
| 302978 | FK60-ER90-S-125 GPF/K | 125 | 32 | 167 | 105 | 54,5 | • | 150 |

\* Two models, depending on how the mounting tube is in relation to the direction of travel.

\* Available also in conductive version upon MOQ



**STANDARD TUBE FITTINGS:**



50 x 50 x 2 mm (EN10219)



Ø 60.3 x 2.9 mm (EN10219)



**Vivax HBC** – The cavities which are important for the function of the locking mechanism are tightly sealed. Foreign objects and dirt cannot penetrate. The remaining area is easily accessible for cleaning and spray disinfection, a plus for hygiene and functional safety. Two large-sized ball bearings give the VIVAX® HBC high resistance to load-bearing and, above all, impact loads, including a test with 10 mm high obstacles with full 130 kg load without failing. A big plus for your safety. The VIVAX® HBC features a polyamide centre and polyurethane tread, 95 Sh A, ensuring durability and reliability in demanding conditions.



**SWIVEL CASTOR WITH CENTRAL TOTAL LOCK**

| Code                         |     |    |     |     |          |   |     |
|------------------------------|-----|----|-----|-----|----------|---|-----|
| <b>KH2Q-54C-Z985-02</b>      | 125 | 32 | 164 | 109 | 32x50    | • | 130 |
| <b>KH2Q-64C-Z985-02</b>      | 150 | 32 | 189 | 121 | 32x50    | • | 130 |
| <b>KH2Q-54C-Z4351-02 (*)</b> | 125 | 32 | 164 | 109 | 27,8x100 | • | 130 |
| <b>KH2Q-64C-Z4351-02 (*)</b> | 150 | 32 | 189 | 121 | 27,8x100 | • | 130 |

Available also in conductive and stainless steel version  
) Long stem coming soon



**SWIVEL CASTOR WITH CENTRAL TOTAL LOCK AND DIRECTIONAL LOCK**


| Code                         |     |    |     |     |          |   |     |
|------------------------------|-----|----|-----|-----|----------|---|-----|
| <b>KH2R-54C-Z985-02</b>      | 125 | 32 | 164 | 109 | 32x50    | • | 130 |
| <b>KH2R-64C-Z985-02</b>      | 150 | 32 | 189 | 121 | 32x50    | • | 130 |
| <b>KH2R-54C-Z4351-02 (*)</b> | 125 | 32 | 164 | 109 | 27,8x100 | • | 130 |
| <b>KH2R-64C-Z4351-02 (*)</b> | 150 | 32 | 189 | 121 | 27,8x100 | • | 130 |

Available also in conductive and stainless steel version  
) Long stem coming soon



Available also in other colour variations.

Stem Ø 32x50 mm, standard hole  
M6x7 mm, switching shaft distance  
34 mm, measured from the tube seat.



Vivax without central locking available as well

# Primacy – Central locking



**Primacy** – The single-wheel swivel castor features a die-cast aluminium load-bearing housing with a polished plastic cover, precision ball bearings in the forkhead, and a central locking system. It has an integrated selection mechanism with a total locking brake or a directional lock. The wheel is equipped with a TPU tyre, Shore A 95, and ball bearings. Primacy offers durability, non-marking wheels, and enhanced swivel and rolling motion.

### SWIVEL CASTOR WITH CENTRAL TOTAL LOCK



| Code                |     |    |     |     |       |   |     |
|---------------------|-----|----|-----|-----|-------|---|-----|
| 398q 29K125v K985NP | 125 | 32 | 158 | 103 | 32x50 | • | 150 |
| 398q 29K150v K985NP | 150 | 32 | 188 | 117 | 32x50 | • | 150 |
| 398q 37K200v K985NP | 200 | 32 | 229 | 156 | 32x50 | • | 150 |

\* Available also in conductive version with thermoplastic rubber tread

### SWIVEL CASTOR WITH CENTRAL TOTAL LOCK AND DIRECTIONAL LOCK



| Code                |     |    |     |     |       |   |     |
|---------------------|-----|----|-----|-----|-------|---|-----|
| 398r 29K125v K985NP | 125 | 32 | 158 | 103 | 32x50 | • | 150 |
| 398r 29K150v K985NP | 150 | 32 | 188 | 117 | 32x50 | • | 150 |
| 398r 37K200v K985NP | 200 | 32 | 229 | 156 | 32x50 | • | 150 |

\* Available also in conductive version with thermoplastic rubber tread

### SWIVEL CASTOR WITH CENTRAL TOTAL LOCK



| Code                 |     |    |     |     |          |   |     |
|----------------------|-----|----|-----|-----|----------|---|-----|
| 398q 29K125v K2351ZA | 125 | 32 | 158 | 103 | 27,8x100 | • | 150 |
| 398q 29K150v K2351ZA | 150 | 32 | 188 | 117 | 27,8x100 | • | 150 |
| 398q 37K200v K2351ZA | 200 | 32 | 229 | 156 | 27,8x100 | • | 150 |

\* Available also in conductive version with thermoplastic rubber tread



Available also in 100 mm

### SWIVEL CASTOR WITH CENTRAL TOTAL LOCK AND DIRECTIONAL LOCK



| Code                 |     |    |     |     |          |   |     |
|----------------------|-----|----|-----|-----|----------|---|-----|
| 398r 29K125v K2351ZA | 125 | 32 | 158 | 103 | 27,8x100 | • | 150 |
| 398r 29K150v K2351ZA | 150 | 32 | 188 | 117 | 27,8x100 | • | 150 |
| 398r 37K200v K2351ZA | 200 | 32 | 229 | 156 | 27,8x100 | • | 150 |

\* Available also in conductive version with thermoplastic rubber tread



Available also as a swivel castor with standard stem fitting.





# Nimbus – Central locking



**Nimbus** – The central locking swivel castor features a die-cast aluminium load-bearing housing with a polished plastic cover and precision ball bearings in the forkhead. Its award-winning, patented design offers durability and hygiene.



reddot design award  
winner



DESIGNPREIS  
2007  
NOMINIERT



## SWIVEL CASTOR WITH CENTRAL TOTAL LOCK

| Code                     |     |    |     |     |       |   |  |     |
|--------------------------|-----|----|-----|-----|-------|---|--|-----|
| <b>399q 38K150v K985</b> | 150 | 32 | 188 | 117 | 32x50 | • |  | 120 |

\* Available also with longer stem 27,8 x 78,5 mm



## SWIVEL CASTOR WITH CENTRAL TOTAL LOCK AND DIRECTIONAL LOCK

| Code                     |     |    |     |     |       |   |  |     |
|--------------------------|-----|----|-----|-----|-------|---|--|-----|
| <b>399r 38K150v K985</b> | 150 | 32 | 188 | 117 | 32x50 | • |  | 120 |

\* Available also with longer stem 27,8 x 78,5 mm



Available also in other colours



Available also as a swivel castor with top plate, without central locking

# TWINTeCH – Central locking



**TWINTeCH** – Pressure die cast aluminium body for lightweight and high load capacity. Wheel centre nylon, polyurethane tread 90 Sh A, precision ball bearing. Available with different fitting stems. Low rolling friction and force to initiate motion.



## SWIVEL CASTOR WITH CENTRAL TOTAL LOCK

| Code              |     |      |    |     |     |       |   |     |
|-------------------|-----|------|----|-----|-----|-------|---|-----|
| <b>305006900M</b> | 125 | 2X18 | 75 | 139 | 105 | 32x52 | • | 135 |
| <b>306006003M</b> | 150 | 2X18 | 79 | 164 | 131 | 32x52 | • | 150 |

\* Available also with a longer stem 28x98 mm

\* Available also in conductive version

\* Available also as a swivel version with a solid metal stem



## SWIVEL CASTOR WITH CENTRAL TOTAL LOCK AND DIRECTIONAL LOCK

| Code              |     |      |    |     |     |       |   |     |
|-------------------|-----|------|----|-----|-----|-------|---|-----|
| <b>305007901M</b> | 125 | 2X18 | 75 | 139 | 105 | 32x52 | • | 135 |
| <b>306007007M</b> | 150 | 2X18 | 79 | 164 | 131 | 32x52 | • | 150 |

\* Available also with a longer stem 28x98 mm

\* Available also in conductive version




## SWIVEL CASTOR WITH CENTRAL TOTAL LOCK

| Code             |     |      |    |     |     |       |   |     |
|------------------|-----|------|----|-----|-----|-------|---|-----|
| <b>305002505</b> | 125 | 2X18 | 75 | 148 | 105 | 25x30 | • | 135 |

\* Available also with a solid metal stem

\* Available also in conductive version



# TT Series – Central locking



**TT series** – High strength PA6 with glass fibre-reinforced body, precision ball bearing at swivel head and wheel centre. Central locking system provides safety and multiple locking functions. Wheel with polyurethane tread (85 Sh A).



SWIVEL CASTOR WITH CENTRAL TOTAL LOCK

| Code             |     |      |    |     |     |       |   |     |
|------------------|-----|------|----|-----|-----|-------|---|-----|
| TT322 R6Ea/19U-G | 75  | 2x12 | 73 | 93  | 78  | 32x50 | • | 90  |
| TT422 R6Ea/19U-G | 100 | 2x16 | 80 | 120 | 100 | 32x50 | • | 100 |


\* Available also in conductive version  
\* Available also with a longer stem 28x98.5 mm



SWIVEL CASTOR WITH CENTRAL TOTAL LOCK AND DIRECTIONAL LOCK

| Code              |     |      |    |     |     |       |   |     |
|-------------------|-----|------|----|-----|-----|-------|---|-----|
| TT320 R6EaJ/19U-G | 75  | 2x12 | 73 | 93  | 78  | 32x50 | • | 90  |
| TT420 R6EaJ/19U-G | 100 | 2x16 | 80 | 120 | 100 | 32x50 | • | 100 |

\* Available also in conductive version  
\* Available also with a longer stem 28x98.5 mm



# CT Series – Central locking



**CT series** – Pressed steel body with double bearing swivel head (precision ball bearing and thrust ball bearing), precision ball bearing at wheel centre. Aesthetic ABS shield, zinc plating finish. Central locking system provides safety and multiple locking functions. Wheel with polyurethane tread (95 Sh A).



SWIVEL CASTOR WITH CENTRAL TOTAL LOCK

| Code             |     |      |    |     |     |       |   |     |
|------------------|-----|------|----|-----|-----|-------|---|-----|
| CT572 R66a W517U | 125 | 2x15 | 78 | 132 | 109 | 32x50 | • | 150 |
| CT672 R66a W617U | 150 | 2x18 | 86 | 155 | 127 | 32x50 | • | 200 |

\* Available also in conductive version  
\* Available also with a longer stem 28x98.5 mm



SWIVEL CASTOR WITH CENTRAL TOTAL LOCK AND DIRECTIONAL LOCK

| Code             |     |      |    |     |     |       |   |     |
|------------------|-----|------|----|-----|-----|-------|---|-----|
| CT570 R66a W517U | 125 | 2x15 | 78 | 132 | 109 | 32x50 | • | 150 |
| CT670 R99a W617U | 150 | 2x18 | 86 | 155 | 127 | 32x50 | • | 200 |

\* Available also in conductive version  
\* Available also with a longer stem 28x98.5 mm



Available also as a swivel castor with a solid metal stem in sizes 125 mm and 150 mm

# 403 Plunger lock castor series



**403** – Twin-wheel castor especially suitable for operating tables. Precision ball bearings in the swivel head and wheel centre ensure easy manoeuvrability and smooth positioning. The assembly features a polyamide centre and polyurethane tread, 95 Sh A, providing durability and reliability. The assembly is based on a hydraulic system (can be ordered separately). Please see below for more information.



Series 403

| Code               |     |      |       |       |    |   |     |
|--------------------|-----|------|-------|-------|----|---|-----|
| 403a 29K100y K00-2 | 100 | 2x30 | 123,5 | 95    | 32 | • | 250 |
| 403b 54CA K00-01   | 125 | 2x32 | 144,3 | 121,5 | 32 | • | 250 |

\* Castor with electrically conductive polyurethane wheels



NEW!

403b

Now also available in 125 mm as a single locking swivel castor.



**HAWE Hydraulik has, in cooperation with Colson developed a hydraulic locking system for this castor.**



Hydraulik Set

## High mobility and secure footing

HAWE developed a new variant of a reliable hydraulic system that can be integrated into twin-wheel castors made by Colson. The system is an enhancement of the proven LF16 floor lock cylinder. Mobile medical devices featuring the integrated LF16 floor lock cylinder can be upgraded by simply replacing the cylinder in the existing hydraulic system.

## Two options for versatile use

1. If the mobile device is not equipped with a hydraulic system, it is recommended to install a complete hydraulic set. This set consists of a hydraulic power unit, a valve

manifold, four cylinders and the associated hydraulic hoses. The valve manifold is available in two versions: the simple variant for level floors and the expanded version for uneven floors.

2. Devices equipped with a hydraulic system for other movements can be easily expanded with a valve manifold, four cylinders and the hydraulic hoses.

Comparable systems operating with integrated cylinders, in addition to the castors, have been successfully applied in operating tables for many years. These reliable products are significantly more stable than conventional systems equipped with blocked castors, especially with heavier patients.

## Advantages of the new product featuring the cylinder integrated in the twin-wheel castor

- Small installation space
- Higher stability under load
- Systems with central locking castors can be easily retrofitted because the cylinder connection dimensions are the same as those of the short standard fixing pin (Ø 32 mm).

# Wheelchair products



**Wheelchair products** – Colson wheelchair products are well-regarded in the mobility aid market, known for their durability, precision, and high-quality materials. Colson manufactures a variety of wheelchair components, including casters specifically designed for both manual and powered wheelchairs.



## ultraLIGHT 315 Low Profile Wheel

Black polypropylene wheel with two precision-sealed ball bearings.  
Black micro cellular polyurethane "puncture proof" tyre.  
Fixing M12 x 1.0 mm Pitch x 12 long thread - 19 mm A/F Axle.

| Code       |     |    |   |    |
|------------|-----|----|---|----|
| 213003002B | 315 | 42 | • | 55 |

Including axle, overall width 63 mm  
Axle fitting torque 35-40 Nm  
Standard ISO 22881  
Wheel in black colour

## ultraLight Wide Profile Castor

Black thermoplastic fork with precision ball bearing  
Black nylon wheel centre with two needle roller bearings  
Black micro cellular polyurethane tyre, 75-85 IRHD  
Fixing M14 x 2 mm Pitch x 22 long & Scotchgrip 2353

| Code       |     |    |     |     |        |   |    |
|------------|-----|----|-----|-----|--------|---|----|
| 217004007B | 190 | 45 | 235 | 140 | M14x22 | • | 60 |

Castor width 91 mm  
Castor in black colour  
Tread hardness 70-85 IRHD  
Standard ISO 7176-8:2014



## extraLIGHT Narrow Profile Castor

Black thermoplastic fork with precision ball bearing  
Black nylon wheel centre with two needle roller bearings and black micro cellular polyurethane tyre, 75-85 IRHD  
Fixing M14 x 2 mm Pitch x 22 long: 24 mm A/F Pin


| Code       |     |    |     |     |        |   |    |
|------------|-----|----|-----|-----|--------|---|----|
| 217005001B | 190 | 29 | 235 | 140 | M14x22 | • | 40 |

Castor width 78 mm  
Castor in black colour  
Tread hardness 70-85 IRHD  
Standard ISO 22881






|                                                                                     |                                    |
|-------------------------------------------------------------------------------------|------------------------------------|
|    | Wheel diameter mm                  |
|    | Wheel width mm                     |
|    | Hub length mm                      |
|    | Total width of a twin wheel        |
|    | Bore diameter mm                   |
|    | Overall height mm                  |
|    | Swept radius mm                    |
|    | Swept radius with brake mm         |
|   | Bolt hole diameter mm              |
|  | Plate length x width mm            |
|  | Hole centres length x width mm     |
|  | Fastening hole diameter mm         |
|  | Stem diameter and length mm        |
|  | Threaded stem diameter x length mm |
|  | Tube fitting inner diameter mm     |
|  | Plain bearing                      |
|  | Ball bearing                       |
|  | Load capacity kg (~10 Newton)      |



Accessories



Alternative products

Please contact us for more details.





#### **USA**

**Colson Group HQ**  
1815 S. Meyers Road  
Suite 750  
Oakbrook Terrace,  
IL 60181  
United States

Tel: +1.800.253.0868  
[www.colsongroup.com](http://www.colsongroup.com)

#### **NORDICS AND BALTICS**

**Oy Mannerin Konepaja Ab**  
Ankkurikatu 1  
10900 HANKO  
Finland

Tel. +358 19 222 001  
[manner@manner.fi](mailto:manner@manner.fi)  
[www.manner.fi](http://www.manner.fi)

#### **POLAND**

**Colson Europe Coöperatief U.A.**

Oddział w Polsce  
Ul. Fabianowska 101  
62-052 Komorniki

Tel +48 61 8 667 012  
[biuro@colson.pl](mailto:biuro@colson.pl)  
[www.colson.pl](http://www.colson.pl)

#### **UNITED KINGDOM**

**Colson UK Ltd**

Bagnall Street, Hill Top  
West Bromwich. B70 0TS

Tel +44 121 556 7221  
Fax +44 121 502 2658  
[sales@colson-castors.co.uk](mailto:sales@colson-castors.co.uk)  
[www.colson-castors.co.uk](http://www.colson-castors.co.uk)

#### **FRANCE**

**Colson SAS**

20 Rue de l'Érable  
78410 Bouafle

Tel. +33 1 30 95 5545  
[contact@colsonse.eu](mailto:contact@colsonse.eu)  
[www.colson-roulettes.com](http://www.colson-roulettes.com)

#### **GERMANY**

**Colson Rollen GmbH**

Industriestraße 8  
42499 Hückeswagen

Tel +49 2192 9368-0  
Fax +49 2192 9368-477  
[info@colson-rollen.com](mailto:info@colson-rollen.com)  
[www.colson-rollen.com](http://www.colson-rollen.com)

#### **BENELUX**

**Colson Europe Coöperatief U.A.**

Generatorstraat 11  
3903 LH Veenendaal

Tel. +31 318-536611  
Fax +31 318-526876  
[info@colson-europe.com](mailto:info@colson-europe.com)  
[www.colson-europe.nl](http://www.colson-europe.nl)

#### **ITALY**

**Colson Italia srl**

Via Ancona 15bis  
60035 Jesi (AN)

Tel. +39 338 3641389  
Fax +39 0731 226631  
[info@colson.it](mailto:info@colson.it)  
[www.colson.it](http://www.colson.it)

